

SWSL0607HD/DC

Standard equipments

Equipments and performance

4X6V/225Ah Battery

Proportional Control

Extendable Platform

Foldable guardrails Platform

Self-lock gate on platform

Solid Tire

Hour Meter

Standard transport forklift hole

Safety maintenance struts

Horn

Flashing Beacon

Action beep

Dual front wheels drive

Pit protection device

Emergency descent system

Emergency Stop Button

Automatic Brake System

Tilt sensor with alarm


Charging protection system

Fault diagnosis system


Overload protection system



Dimensions



Norking height*		8m
Α	Platform height maximum	6m
В	Platform height (stowed)	1.05m
С	Platform length	1.7m
	Slide-out platform extension deck	0 . 9m
D	Platform width	0.74m
Е	Stowed height (rails up)	2.17m
	Stowed height (rails down)	1.79m
F	Overall length	1.86m
G	Overall width	0.76m
Н	Wheelbase	1 . 38m
I	Ground clearance (stowed)	0.07m
J	Ground clearance (raised)	0.02m



Standard machines							
SWSL0607HD	Standard equipments						
SWSL0607DC	Standard equipments						
Options available							
*Options available for a built on order machines in Belgium or assembly in factory.							
Air line to platform							
AC power to platform							
GPS tracking system							
Platform working lights							
Manitenance-free battery							
Lithium battery and management system							
Intelligent interconnection system							
Attachments							
		Weight (kg)	Specification				
Warranty							
Standard warranty							
1	1 year or 1000h FULL + 2nd year (only Power train)						